

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facility Management & Technology Society 10-12, 2015 • Las Vegas

Addressing Moisture in Concrete for Roofing and Flooring Applications

Session W1.47 – Wednesday, 11 March 2015, 9:00 am to 9:50 am, Room 347

Presented by
David S. Slick, PE
Joseph D. Rogers, PE
Philip K. Frederick, PE
Simpson Gumpertz & Heger Inc.

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facility Management & Technology Society 10-12, 2015 • Las Vegas

Abstract

Repair of roofing and floor finish failures are typically very costly, time consuming, and disruptive to facility operations. This presentation will help building owners, facility managers, architects, and contractors understand the causes of concrete substrate moisture-driven roofing and flooring failures, and how the failure mechanisms must be considered in the design or repair process. Both the roofing and flooring industries have come to understand the importance of addressing moisture in concrete substrates for roofing and moisture-sensitive flooring applications.

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facility Management & Technology Society 10-12, 2015 • Las Vegas

Abstract

This presentation will discuss the science behind moisture drive through concrete substrates, the implications of ignoring such moisture issues in both roofing and flooring systems, and methods for consideration to mitigate these moisture issues in roofing and flooring substrates. We will augment this presentation with case studies of concrete substrate moisture-driven roofing and flooring failures and repairs. The presenters will discuss: similarities between identifying and testing for moisture in concrete substrates in roofing and flooring systems; common considerations for causes of moisture-driven roofing and flooring failures; similar strategies for repairing failed roofing systems and floor finishes; and common considerations that must be addressed during concrete substrate moisture-driven roofing and flooring repair projects.

Learning Objectives

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

At the end of this presentation, participants will be able to:

1. Understand the importance of addressing moisture in concrete substrates for roofing and flooring applications.
2. Recognize concrete substrate moisture-driven roofing and flooring failure mechanisms and understand how to address such mechanisms in roofing and flooring repair design.
3. Identify critical issues to be considered during design and repair of roofing and flooring systems over a moisture-laden concrete substrate.
4. Select a roofing or floor finish repair strategy that addresses existing conditions and meets performance, operational and budgetary requirements.

Presentation Outline

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- **Moisture in Concrete Substrates**
 - Why Do We Care?
 - Sources of Moisture
 - Some Reasons for Increase in Roofing and Flooring Failures
- **Similarities in Identifying and Testing for Moisture**
 - Perform Proper Moisture Testing
 - Ideas to Minimize the Chance of Failures
- **Case Studies**
- **Summary: Concrete Substrate Moisture Considerations**

Presentation Outline

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- **Moisture in Concrete Substrates**
 - Why Do We Care?
 - Sources of Moisture
 - Some Reasons for Increase in Roofing and Flooring Failures
- **Similarities in Identifying and Testing for Moisture**
 - Perform Proper Moisture Testing
 - Ideas to Minimize the Chance of Failures
- **Case Studies**
- **Summary: Concrete Substrate Moisture Considerations**


Moisture In Concrete Substrates


BUILDING OPERATING MANAGEMENT'S
NFMT2015
Nondestructive Moisture Management & Technology


Why Do We Care?


- Roofing failures
 - Excessive residual moisture in concrete substrate can be a primary cause of rigid insulation and roofing membrane detachment











Moisture In Concrete Substrates

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Field Management & Technology Summit 10-12/2015 - Portland


Why Do We Care?

- Roofing failures
 - Excessive residual moisture in concrete substrate can be a primary cause of rigid insulation and roofing membrane detachment
- Flooring Failures
 - Excessive residual moisture in concrete substrate can be a primary cause of flooring failure









Moisture in Concrete Substrates

BUILDING OPERATIONS MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Sources of Moisture

- Roofing
 - Residual moisture in concrete from placement
 - Unprotected deck after initial placement or tear-off
 - Leakage due to failed roofing systems
- Flooring
 - Underlying soil
 - Residual moisture in concrete from placement
 - Cleaning and maintenance
 - Ambient conditions

Moisture In Concrete Substrates BUILDING OPERATING MANAGEMENT'S
NFMT2015
Nondestructive Management & Technology Month 10-12, 2015 - Portland

Some Reasons for Increase in Roofing and Flooring Failures

- Change in materials





Change in Materials

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Hot asphalt as an adhesive
 - Traditional product with a proven track record
 - Typically, continuous application over entire surface
- Foamed adhesive
 - Contemporary product that can provide reliable performance
 - Is different from traditional hot asphalt used as adhesive
 - Requires different installation techniques
 - Installation in accordance with manufacturer's recommendations is key
 - Less tolerant of moisture in concrete substrate



Change in Materials

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Asphalt cut back adhesive
 - Traditional product with a proven track record
 - Tolerant of some moisture in concrete substrate
- Water-based adhesive
 - Contemporary product that can provide reliable performance
 - Is different from traditional asphalt cut back adhesive
 - Installation in accordance with manufacturer's recommendations is key
 - Less tolerant of moisture in concrete substrate

Moisture In Concrete Substrates
BUILDING OPERATING MANAGEMENT'S
NFMT2015



Some Reasons for Increase in Roofing and Flooring Failures

- Change in materials
- Blended cement (fly ash) concretes

Concrete with
and without Fly Ash
BUILDING OPERATING MANAGEMENT'S
NFMT2015

Concrete microstructure without fly ash at 200X magnification.

Concrete microstructure with 20% fly ash at 200X magnification.

Blue color in paste indicates voids. Less voids in fly ash concrete, so slower drying and more dense.

Moisture In Concrete Substrates
BUILDING OPERATING MANAGEMENT'S
NFMT2015


Some Reasons for Increase in Roofing and Flooring Failures

- Change in materials
- Blended cement (fly ash) concretes
- Use of lightweight concrete

Normal Weight vs. Lightweight Concrete

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- 110 to 115 pcf vs. 145 to 150 pcf
- Expanded slate and shale aggregate



Normal-Weight vs. Lightweight Concrete

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas



Fig. 6: RH history for Study 1, Nonconditioned Environment

Both NW and LW concrete may require
long drying time, whether outdoors or in
non-conditioned environment

From Concrete International, January 2012

Moisture In Concrete Substrates

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Some Reasons for Increase in Roofing and Flooring Failures

- Change in materials
- Blended cement (fly ash) concretes
- Use of lightweight concrete
- Fast track construction

Presentation Outline

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- **Moisture in Concrete Substrates**
 - Why Do We Care?
 - Sources of Moisture
 - Some Reasons for Increase in Roofing and Flooring Failures
- **Similarities in Identifying and Testing for Moisture**
 - Perform Proper Moisture Testing
 - Ideas to Minimize the Chance of Failures
- **Case Studies**
- **Summary: Concrete Substrate Moisture Considerations**

Similarities in Identifying and Testing for Moisture

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Roofing manufacturers and roofing adhesive manufacturers typically require installation over a "dry" concrete substrate
 - No definitive criteria for compliance, but we can typically rely on the flooring industry for some guidance
- Flooring manufacturers and flooring adhesive manufacturers typically require a concrete substrate compliant with the following criteria
 - Moisture Vapor Emission Rate (MVER) no greater than 3 lb/1,000 SF/24 hrs, and/or
 - Relative Humidity (RH) no greater than 75%
- So how do we comply?

ASTM Moisture Test Standards

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- ASTM F1869 – *Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride*
- ASTM F2170 – *Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes*

ASTM F1869 –
“Moisture Vapor Emission Rate”

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- ASTM F1869 - Standard Test Method for Measuring Moisture Vapor Emission Rate of Concrete Subfloor Using Anhydrous Calcium Chloride
 - Quantitative; 60 to 72 hour duration



ASTM F1869:
Limitations of Test

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas


- No documented scientific basis.
- No calibration procedures or standard reference.
- Only measures thin layer (1/2 in.) on surface of concrete.
 - Not a good indication of trapped moisture in lightweight concrete


ASTM F2170 –
“Internal Concrete RH”


BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- ASTM F2170 – Standard Test Method for Determining Relative Humidity in Concrete Floor Slabs Using in situ Probes
 - Quantitative; test standard requires 72 hours (to reach equilibrium)









ASTM F1869 vs. ASTM F2170

BUILDING OPERATING MANAGEMENT'S
NFMT2015
Technical Building Management & Technology Summit 10-12, 2015 • Las Vegas

	High RH	Low RH
High MVER		
Low MVER		

- **Average calculation not applicable, maximum value must be below limit**
 - Can consider breaking test area up into zones, but must be clearly defined by location, concrete pour, etc.

ASTM D4263 –
“Plastic Sheet Method”BUILDING OPERATING MANAGEMENT'S
NFMT2015
Technical Building Management & Technology Summit 10-12, 2015 • Las Vegas

- ASTM D4263 – Standard Test Method for Indicating Moisture in Concrete by the Plastic Sheet Method
 - Qualitative - Minimum 16 hour duration
 - Results can vary greatly, depending on when and where test is performed
 - Not used in the flooring industry



Electric Resistance
MeasurementBUILDING OPERATING MANAGEMENT'S
NFMT2015
Technical Building Management & Technology Summit 10-12, 2015 • Las Vegas

- Electric resistance measurement
 - Example: Tramex CME 4
 - Can be used to estimate concrete substrate moisture content when calibrated with MVER and RH tests
 - Particularly useful in roofing industry (after calibration) due to test time constraints of MVER and RH tests
 - Not used in the flooring industry
 - Not an industry standard test




Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology March 10-12, 2015 • Baltimore

- Plan ahead

Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015



Typical Construction Timeline

Planning ahead for flooring installation

Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete

Concrete Mix Design

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Water/Cement Ratio
 - 0.40 W/CM for normal weight slabs
 - 0.45 W/CM for lightweight slabs
- Consider using water-reducing admixtures
 - Superplasticizers / high-range water reducing admixtures
- Prohibit addition of water in the field



Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete
- Consider the concrete curing method

Concrete-Curing Methods

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- ~~Moisture Addition (water curing or wet covering)~~
 - Adds water to system.
 - May stain or discolor the slab.
- ~~Liquid Membrane Forming Curing Compounds~~
 - Do not allow concrete to begin drying until removed.
 - Act as a bond-breaker and prevent adhesion of finishes.
- Moisture-Retaining Covers
 - Can be removed as soon as cure is complete.
 - Can be a nuisance and potential hazard during construction.

Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facility Management & Technology Summit 10-12, 2015 • Anaheim

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete
- Consider the concrete curing method
- Use a vapor retarder for roofing applications


Vapor Retarder for Roofing Applications

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facility Management & Technology Summit 10-12, 2015 • Anaheim

- Vapor Retarder
 - Limit residual moisture in the concrete substrate
 - Added benefit: will limit moisture from the space below from entering the roofing system
- Common Vapor Retarders
 - Hot rubberized asphalt
 - Modified bitumen
 - Self-adhered membrane
 - EPDM/Neoprene
 - Others








Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Nashville

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete
- Consider the concrete curing method
- Use a vapor retarder for roofing applications
- Use a moisture mitigation system for flooring applications
 - Use a product intended for the purpose
 - Make sure it gets installed properly



Types of Moisture Mitigation

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Flooring Management & Technology Summit 10-12, 2015 • Las Vegas

Type of Mitigation System	Typical Manufacturer Limitations	Typical Surface Preparation Requirements
Water-Based Acrylic Coating	Low	Cleaning.
Penetrating Treatment	Low	Cleaning and sanding.
Reactive Penetrant	Medium	General cleaning.
Loose-Laid Sheet	Medium	General cleaning.
Underlayment System	High	Shotblasting.
Modified Epoxy Coating	High	Shotblasting.
Concrete Admixture	NA	NA

Moisture Mitigation System Selection


BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Flooring Management & Technology Summit 10-12, 2015 • Las Vegas

- A long track record of success and a manufacturer that will work closely with you
- Epoxy-based, topical products seem to have best performance
 - Continuous coating
 - High pH tolerant
 - ASTM E96 < 0.1 perms
 - **ASTM F3010-13 (Two-Component Mitigation Coatings)!**
- Clear, specific, and simple installation instructions.

Mitigation System System Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Surface preparation (shot blasting)
- Leveling underlayment / "blotter" layer
- Assume \$5 to \$10 per square foot
- Include in bid upfront




1. Concrete
2. Mitigation Coating
3. Underlayment Primer
4. Cementitious Underlayment
5. Flooring with Adhesive

Other Flooring Options for Mitigating High Moisture Levels

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Chose a different, more-permeable flooring system
- Upgrade adhesives



Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete
- Consider the concrete curing method
- Use a vapor retarder for roofing applications
- Use a moisture mitigation system for flooring applications
 - Use a product intended for the purpose
 - Make sure it gets installed properly
- **Wait longer**
 - Not an option for roofing applications

Ideas to Minimize the Chance of Failures

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete
- Consider the concrete curing method
- Use a vapor retarder for roofing applications
- Use a moisture mitigation system for flooring applications
 - Use a product intended for the purpose
 - Make sure it gets installed properly
- Wait longer
 - Not an option for roofing applications
- “Accelerate” drying of the concrete substrate
 - Only applicable for flooring applications

Ideas to Minimize the Chance of Failures


BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- Plan ahead
- Use low w/c ratio concretes without fly ash
 - Be aware of extra moisture in lightweight concrete
- Consider the concrete curing method
- Use a vapor retarder for roofing applications
- Use a moisture mitigation system for flooring applications
 - Use a product intended for the purpose
 - Make sure it gets installed properly
- Wait longer
 - Not an option for roofing applications
- “Accelerate” drying of the concrete substrate
 - Only applicable for flooring applications
- Perform proper moisture testing

Presentation Outline

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas


- **Moisture in Concrete Substrates**
 - Why Do We Care?
 - Sources of Moisture
 - Some Reasons for Increase in Roofing and Flooring Failures
- **Similarities in Identifying and Testing for Moisture**
 - Perform Proper Moisture Testing
 - Ideas to Minimize the Chance of Failures
- **Case Studies**
- **Summary: Concrete Substrate Moisture Considerations**







































































Presentation Outline

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

- **Moisture in Concrete Substrates**
 - Why Do We Care?
 - Sources of Moisture
 - Some Reasons for Increase in Roofing and Flooring Failures
- **Similarities in Identifying and Testing for Moisture**
 - Perform Proper Moisture Testing
 - Ideas to Minimize the Chance of Failures
- **Case Studies**
- **Summary: Concrete Substrate Moisture Considerations**

Summary: Concrete Substrate Moisture Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Roofing

- **Moisture in the roofing assembly**
 - Can be a primary cause of rigid insulation and roofing membrane detachment
 - Can weaken and deteriorate the organic insulation facer, resulting in cohesive failure in the insulation facer well below the code required design wind pressures
 - May contribute to bowing insulation boards
 - Can result in the development of biological growth within the roofing assembly

Summary: Concrete Substrate Moisture Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Roofing

- **Need reliable quantitative testing to establish condition of concrete substrate prior to roofing installation**
 - Ensure the roof deck is “dry” prior to roofing installation
 - Different from flooring applications (due to time constraints, exposure, etc.)

Summary: Concrete Substrate
Moisture Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Roofing

- Provide a vapor retarder where required to limit the amount of moisture entering the roofing assembly
 - Design must prevent moisture from becoming trapped in roofing assembly
 - Prevents residual moisture in concrete substrate from diffusing into roofing assembly
 - Some vapor retarders can also function as an air barrier

Summary: Concrete Substrate
Moisture Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Flooring

- Moisture in the flooring substrate
 - Can be a primary cause of flooring failure
 - Can be from sources other than concrete, such as underlying soil or ambient conditions
 - Can be dependent on
 - Exposure to weather or construction water
 - Amount of time concrete substrate is allowed to naturally dry
 - Amount of time installation area has been enclosed, with HVAC system operational

Summary: Concrete Substrate
Moisture Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Flooring

- Need reliable quantitative testing to establish condition of concrete substrate prior to flooring installation
 - Ensure the concrete substrate moisture content meets flooring manufacturers' recommendations prior to flooring installation

Summary: Concrete Substrate Moisture Considerations

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

Flooring

- Provide a moisture mitigation membrane where required to limit the amount of moisture entering the flooring assembly
 - Prevents residual moisture in concrete substrate from affecting flooring products
 - Required if there is moisture in the concrete substrate greater than the flooring manufacturer's recommendations

Learning Assessment Questions

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

1. It is important to address moisture in concrete substrates for roofing and flooring applications.

- **True** False

2. Moisture in the concrete substrate can result in failure of roofing or flooring systems.

- **True** False

Learning Assessment Questions

BUILDING OPERATING MANAGEMENT'S
NFMT2015
National Facilities Management & Technology Summit 10-12, 2015 • Las Vegas

3. No similarity exists between potential damage to a roofing system from moisture in the concrete roofing substrate and potential damage to a flooring system from moisture in the concrete flooring substrate.

- True **False**

4. Repair of a failed roofing or flooring system damaged as a result of moisture in the concrete substrate can be expensive.

- **True** False

